

Z-Perform™ 1000T 190 Tag

Media Type	Label		Adhesive Type	Permanent	
	Receipt			Removable	
	Tag	✓		No Adhesive	✓
	Wristband			Environment	Indoor
Material Type	Paper	✓	Outdoor		
	Synthetic		Properties	Cold Temperature	✓
Printing Technology	Direct Thermal (no Ribbon Required)			Deep Freeze	✓
	Thermal Transfer (Ribbon Required)	✓		High Temperature	
Finish	Matte	✓		Ultra High Temperature	
	Gloss			High Tack	
				Chemical Resistance	-

Additional Features

- Good print quality when printed with Zebra 2300, 2100, 3400 and 3200 ribbons with a recommended Zebra printer
- BfR Recommendation XXXIV for direct contact with dry, moist and non-fatty foodstuffs
- Complies with DIN EN 71 part 3 and part 9 as the product does not release any heavy metals and does not contain prohibited amines or colourants
- BPA free

Suggested Applications

- Indoor cold temperature labelling
- Visitor identification tags
- Admission tickets
- Warehouse and inventory control tags
- Shop floor / work in progress tracking tickets
- Shelf-edge tags
- Packaging inserts
- Pallet tagging

Technical Specifications

	Description	Caliper
Facestock	190gsm matte white uncoated paper	170 microns
	Total	170 microns ±10%

Recommended Zebra Printers: Desktop, mid-range and high-performance thermal printers

Recommended Zebra Ribbons: 2300, 2100, 3400, 3200

Minimum Application Temperature: 0°C
When the label is applied, the environment and surface should be above this temperature

Service Temperature Range: -43°C to 93°C
Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

Recommended Storage Conditions: 1 year duration when stored at 0°C to 21°C at 35% to 50% RH
Storage of product before use

Expected Life Span in Application: Indoor use, for 1 year+
Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order from the ZipShip price list or order sample roll SAMPLE5284.